
09 September 2017

TEST REPORT



SMART COOLING™ PRO10 SYSTEM

NOVOTEL, IBIS Hotels

Test Participants:

Project name: NOVOTEL / IBIS FUJAIRAH Location: Fujairah, UAE

Organization Responsible: Ecovis Engineering Ltd

Compiled by: Alexander Alzamora

Table of Contents

Introduction:	. 3
Main components:	. 4
Measuring instruments:	. 5
Testing Smart Cooling™ PRO 10	6
Testing data:	. 7
Conclusion:	10

Introduction:

Type of structure: Hotel complex with air-cooled water chillers.

Cooling units: Air cooled water chiller Petra APSa 325-2.

Chiller booster: Smart Cooling™ PRO 10, adiabatic technology with condenser protec-

tion (BY70).

Chillers were retrofitted with the intelligent adiabatic *Smart Cooling*™ system to reduce their electricity consumption and increase COP (Coefficient of Performance) efficiency.

The intelligent adiabatic $Smart\ Cooling^{TM}$ system combines an adiabatic evaporative pre-cooling process and condenser protection with mechanical air filtration. The intelligent adiabatic $Smart\ Cooling^{TM}$ system is mounted externally in front of the condensers of the cooling equipment. $Smart\ Cooling^{TM}$ initiates the adiabatic process even before the mechanical cooling kicks in and the equipment receives a temperature-reducing fine mist of processed water that within the cooling circuit.

Smart Cooling™ ensures 100% condenser protection from direct contact with water.



System installation on chiller condensers



Existing chillers on site



Main components:

Smart Cooling ™ comprises the following key components: protective membranes, water treatment and recirculation systems, high-pressure water pump, control unit, high-pressure nozzle panels, fasteners, and fixings.

- Protective membranes cover the condenser surface, preventing direct water contact.
- Water system purifies and sterilizes water to prevent mineral buildup and bacteria.
- **Pump** provides 70 bar pressure.
- Control unit regulates operation via real-time data (temperature, humidity, chiller parameters).
- Nozzles spray 5-40 µm droplets.
- A set of fasteners and fixings ensure the compatibility of the equipment with the chiller.



Measuring instruments:

All measurements were collected using the following set of professional diagnostic tools:

- **ENICOPE analytics energy measurement system** main platform for real-time energy logging (kWh, temperatures, humidity, load profiles).
- Cooling power calculator modules for evaluating cooling capacity and operating parameters of the chiller.
- **Ultrasonic flowmeter RIF 600** non-intrusive ultrasonic sensor for measuring chilled-water flow.
- Thermal camera Testo 882 used to detect condenser surface temperatures and visualize temperature drop provided by Smart Cooling™.
- Clip-on current probes (ENICOPE sensors) for measuring electrical load and phase consumption on chiller power lines.



ENICOPE analytics

Cooling power calculator



Thermal camera Testo 882



Current sensors, clip-on probes



Ultrasonic flowmeter RIF 600



Testing Smart Cooling ™:

Step 1 — Installation of data logging equipment

A data logger was installed on the **PETRA APSa 325-2** chiller system to collect all real-time energy consumption and operational parameters.

Measurements were recorded using the ENICOPE analytics energy monitoring platform.

Step 2 — Measurement period with Smart Cooling ™ OFF

The first 4 days (96 hours) were monitored without the Smart Cooling[™] system. During this period:

- Electrical consumption: 44,264 kWh
- Water consumption: 0 m³
- Average temperature: 36.56°CAverage humidity: 39.9% RH

Step 3 — Activation of *Smart Cooling* ™ system

The adiabatic pre-cooling system Smart Cooling ™ BY-70 was switched ON

Step 4 — Measurement period with Smart Cooling™ ON

The next 4 days (96 hours) were monitored with the system operating.

During this period:

- Electrical consumption: 34,955 kWh
- Water consumption: 69 m³
- Average temperature: 36.28°C
- Average humidity: 41.32% RH

Step 5 — Comparative analysis

Energy consumption for both 4-day periods was compared under similar temperature and humidity conditions.

The measured energy savings delivered by *Smart Cooling*™ over the 4-day **ON** period were: 9,308 kWh saved



Air cooled water chiller Petra APSa 325-2




Testing Data:

Comparison of total KWh consumed by rack «B» chiller system for 4 consecutive days with adiabatic pre-cooling system **OFF** – to 4 consecutive days with adiabatic system **ON** (with comparative temp. & RH data).

• Equipment tested: Air cooled water chillers Petra APSa 325-2.

Date	System	Time	Average	Average	Saving	Saving	Hrs used	KWh used	Rain	m3 Water
			Temp C	Humidity HR%	KWh	%	per test	pertest		consumption
08.09.2017	OFF	15:01	36.20	41.55	0	0	22:15:00	11429	No	0
09.09.2017	OFF	15:00	36.01	39.47	0	0	45:15:00	11159	No	0
10.09.2017	OFF	15:04	36.60	38.52	0	0	72:00:00	10839	No	0
11.09.2017	OFF	15:00	37.42	40.40	0	0	96:00:00	10837	No	0
Total					0			44264		0
Date	System	Time	Average	Average	Saving	Saving	Hrs used	KWh used	Rain	m3 Water
			Temp C	Humidity HR%	KWh	%	pertest	pertest		consumption
15.09.2017	ON	14:00	36.09	42.58	2137	19%	96:00:00	9292	No	17.42
16.09.2017	ON	14:03	36.69	45.40	2209	21%	120:00:00	8868	No	15.80
17.09.2017	ON	14:05	35.25	39.57	2501	23%	144:00:00	8387	No	18.34
18.09.2017	ON	14:00	36.49	43.04	2379	22%	167:00:00	8458	No	17.99
Total					9226	21.25%		35005		69.55

Comparison of total KWh consumed by rack «B» chiller system for 4 consecutive days with adiabatic pre-cooling system **OFF** – to 4 consecutive days with adiabatic system **ON** (with comparative temperature & RH data).



Chillers energy consumption

16.09.2017 Smart Cooling[™] system ON vs 09.09.2017 Smart Cooling[™] system OFF

San	Lagrana A	Adiabatic on	Adiabatic OFF	Differnece in %	Adiabatic on	Adiabatic OFF	Differnece in %	Adiabatic on	Adiabatic OFF	Differnece in %
date	timestamp	Chiller6-6	chiller 6 09/09/2017		chiler 2 - E	chiler 2 09/09/2017	200000000000000000000000000000000000000	chiller 3 - E	chiller 3 09/09/2017	
16-09-2017-00:0	1505505600	120244	226359	22%	153579	151486	25%	107621	90565	
16.09.2017-01:0	1505509200	145680	222909	34%	95572	150125	36%	105527	50356	
18.09.2017.02.0	1505512800	147089	225515	34%	92127	149511	19%	85163	38476	
16 09 2017 05:0	1505516400	145309	221838	54%	91080	190535	19%	87754	47520	
16.09.3017.04.0	1505520000	146356	219115	33%	90557	150230	40%	68162	38316	
16 09 2017 05:0	1505523600	180804	219535	27%	89824	150544	40%	74120	51089	
16-09-3017-06:0	1905827200	188312	221000	17%	92546	180649	19%	AGOUR	51717	
16:09.2017 07:0	1505530800	179124	226865	21%	98279	153580	19%	80925	52345	
18-09-2017 08:0	1505534400	177554	278580	36%	215475	177554	25%	84360	61558	
16:09:3017:09:0	1505538000	184045	283186	35%	120299	184778	35%	110256	62186	
16:09:2017 10:0	1505541600	185029	179941	34%	219495	185824	36%	110238	61144	
16:00:2017 11:0	1505545200	188651	284338	34%	120289	184045	35%	111790	61662	
16:09:2017:12:0	1505548800	191581	279512	31%	522173	184359	34%	113274	62081	
16.69.2017 15:0	1505552400	188232	282244	33%	121231	183207	34%	113170	62605	
16-09-2017 14:0	1505556000	187290	278789	33%	121126	182370	34%	113379	62081	
16:09:2017 15:0	1505559600	197340	278580	29%	120603	173262	30%	115274	81358	
16:09:2017 16:0	1505563200	231469	282139	18%	118300	163526	28%	110762	50929	
16 09 2017 17:0	1505566800	234975	279103	19%	117881	161015	27%	110543	80615	
16 09 2017 18 0	1505570400	220896	275125	20%	115682	160804	28%	108354	59778	
16 09 2017 19:0	1505574000	217650	277951	22%	113379	158919	29%	74749	51757	
16 09 2017 20:0	1505577600	217251	269158	1996	312846	158834	29%	85117	62395	
18.09.2017.21:0	1505581200	215342	271879	21%	211399	255778	28%	58189	52136	
16-09-2017-22:0	1505584800	218917	268948	19%	212125	155150	28%	54908	26068	
16:09:2017.23:0	1505588400	152638	249581	39%	504271	154105	32%	54189	49957	
	TOTAL IN KW/H	4457	6200	28%	2625	3930	33%	2210	1299	
Difference in KW/H		1743			1306	Total Company		-912		
Total	onsumtion OFF 24M					1 14 29	17	1.10	1	
Total	consumtion ON 24H					92 92				19%
Difference Ke/I	total 3 units in 24h					21 37				

Chillers energy consumption

17.09.2017 Smart Cooling[™] system ON vs 10.09.2017 Smart Cooling[™] system OFF

Same and the same		Adiabatic on	Adiabatic OFF	Differnece in %	Adiabatic on	Adiabatic OFF	Differnece in %	Adiabatic on	Adiabatic OFF	Differnece in %
date	timestamp	Chiller 6 - E	Chiller 610/09/-13/09		chilter 2 - E	Chiller 5 10/09/-13/09		chiller 3+E	Chiller 6 10/09/ - 13/09	
17.09.2017.00.00	1505592000	114217	233354	51%	92022	153057	40%	63756	32768	
17.09.2017.01.00	1505595600	117931	233144	45%	90661	154103	41%	63861	40620	
17.09.2017.02.00	1505599200	174099	235447	26%	92650	154103	40%	65012	25858	
17.09.2017.03.00	1505602800	185301	231469	20%	91604	152114	40%	65536	26476	
17.09:2017 04:00	1505606400	182360	229589	21%	91708	152638	40%	64698	21252	
17 09 2017 09 00	1505610000	182893	229375	20%	96733	151591	36%	61558	27952	
17.09.2017.06.00	1505613600	182998	228957	20%	112542	151905	26%	67734	47948	
17.09.2017.07.00	1505617200	188546	233458	19%	114321	153685	26%	76005	52868	
17 09 2017 08 0	1505620800	222780	240787	7%	115473	175251	3496	109087	55381	
17.09.2017.09.00	1505624400	226653	255338	11%	117567	191687	39%	112546	63023	
17.09 2017 10 0	1505628000	233563	262667	11%	120603	183626	34%	114217	63337	
17.09.2017 11:00	1505631600	234505	262248	11%	121440	185720	35%	112227	54908	
17.09.2017.12.00	1505€35200	233668	262143	11%	122173	169388	28%	113274	63023	
17,09,2017 13-00	1505638800	232621	265912	13%	122058	161432	2496	114635	63547	
17.09.2017.14.00	1505642400	181113	271984	33%	120154	164468	2796	115892	63547	
17.09.2017.15.00	1505646000	151277	272298	44%	117462	183521	36%	115578	52081	
17.09.2017 18:00	1505649600	153475	272194	44%	121440	177135	31%	96001	61024	
17.09.2017 17:00	1505653200	150649	278161	46%	119870	170854	30%	68572	59883	
17 09 2017 18 00	1505656800	145205	267987	46%	118195	156721	25%	67211	42190	
17/09/2017 19:00	1505660400	146880	264028	44%	116310	157139	26%	66792	52240	
17.09.2017 20.00	1505664000	140389	263818	47%	109610	156825	30%	67106	51717	
17.09-2017-21-00	1505667600	143844	262353	45%	109401	155883	30%	79460	51507	
17.09.2017 22.00	1505671200	143949	261934	45%	102491	155360	34%	78622	37898	
17 09 2017 23 00	1505674800	141331	250313	44%	74539	154941	52%	77575	33710	
	TOTAL IN KW/H	4220	6069	30%	2611	3923	33%	2037	1167	
Di	fference in KW/H	1849			1312			-870		
Total c	onsumbon OFF 24H				4	1 11 59				
Total	consumpion ON 24M					88 68				21%
Difference Kw/h	total 3 units in 24h					22 90				



Chillers energy consumption

18.09.2017 Smart Cooling[™] system ON vs 11.09.2017 Smart Cooling[™] system OFF

		Adiabatic on	Adiabatic OFF	Differnece in %	Adiabatic on	Adiabatic OFF	Differnece in %	Adiabatic on	Adiabatic OFF	Differnece in 9
date	timestamp	Oilers-E	Chiller 6 11/09/2017		chiler2-E	chiller 2 08/09/2017		dilars-E	chiller 5 08/00/2017	
18 09 2017 01:00	1505682000	137353	235343	42%	72445	153999	53%	79885	19837	
18.09 2017 02:00	1505685600	141750	150517	39%	71713	155360	54%	79622	41981	
18.09.2017.03:00	1505689200	133573	232830	42%	71294	154627	54%	78413	53710	
18 09:2017 04:00	1505691800	141017	126538	38%	71922	152524	53%	79517	19591	
18.09.2017.05:00	1505696400	143064	228224	38%	72627	151905	53%	78622	24288	
18 09 3017 06:00	1505700000	135992	226653	40%	72541	152324	53%	78821	57793	
16:09.2017.07:00	1505703600	184372	250632	29%	81972	153999	47%	79250	50670	
18.09.2017 08:00	1505707200	189474	240577	24%	313274	187709	40%	80716	58522	
18.09.2017.09:00	1505710800	216741	272508	23%	114112	176507	35%	94325	56478	
18.09.2017.10:00	1505714400	228957	176800	17%	116520	143425	19%	110867	66897	
16.09.2017 11:00	1505718000	221504	277742	20%	214112	164258	31%	109191	57734	
18.09.2017 12:00	1505721600	144577	279894	48%	154112	182684	38%	109191	67794	
18.09.2017 13:00	1505725300	133480	279512	52%	212065	182056	38%	90033	57630	
18.09.2017 14:00	1505728800	138610	279208	44%	112960	179543	37%	79525	67650	
18 09 2017 15:00	1505732400	187709	277533	32%	112856	179962	37%	101340	67630	
18.09.1017 15:00	1505736000	217964	280359	22%	110971	179657	38%	115264	67001	
18 69 2017 17:00	1505759600	212520	283500	25%	110029	176601	38%	109401	65641	
18.09-2017 18:00	1505743200	207914	271147	23%	108563	174099	38%	75795	51976	
18.09.2017 19:00	1505746800	206558	265590	22%	108577	154941	30%	70099	55067	
18.09.2017 20:00	1505750400	207391	251465	18%	109401	155674	30%	110134	19465	
18.09.2017 21:00	1505754000	204985	256076	13%	106354	157454	31%	98304	52031	
18 09 2017 22:00	1505757600	161897	233040	30%	96838	155569	38%	67211	51193	
18.09/2017 23:00	1505761100	138714	232411	40%	89910	153475	42%	68572	48681	
	TOTALIN KW/H	4023	5849	31%	2267	3780	40%	2947	1209	
	Difference in KW/H	1825			1513			-837		
Total co	onsumtion OFF 24H					1 08 39				
Total c	onsumtion ON 34H					83 37				23%
Difference Kw/h	total 3 units in 24h					25 01				

Chillers energy consumption

19.09.2017 Smart Cooling[™] system ON vs 12.09.2017 Smart Cooling[™] system OFF

	nu - D	Adiabatic on	Adiabatic OFF	Differnece in %	Adiabatic on	Adiabatic OFF	Differnece in %	Adiabatic on	Adiabatic OFF	Differnece in 9
date	timestamp	Chiler 6-E	Chiller 5 12/09/2017		chiler2-E	chiller 2 08/09/2017		chiller 3 - E	chiller 5 00/09/2017	
19.09 2017 00:00	1505764800	140705	230108	39%	89510	143111	37%	68792	40410	
19.09.2017.01:00	1505768400	142483	216499	34%	89510	141959	37%	67211	37060	
19.09.2017 02:00	1505772000	146461	212102	31%	88149	143116	38%	66475	43237	
19 09 2017 03:00	1505775600	141545	211264	33%	89029	143116	37%	69725	28476	
18.09 2017 94:00	1505779200	137582	210950	35%	90136	141483	37%	63467	18425	
19.09.2017 05:00	1505782800	141017	209275	33%	90452	141331	36%	56781	21199	
19.09.2017.06:00	1505786400	154886	208856	21%	101957	142169	27%	80821	27219	
19.09.2017.07.00	1305790000	170854	211997	19%	109914	143544	24%	80192	51403	
19.09.2017 08:00	1505793600	178157	235238	26%	112437	147927	24%	81867	55287	
19.09.2017 09:00	1505797200	177884	276591	36%	154321	164386	21%	88857	60092	
19.09.2017 10:00	1505800800	213567	181548	24%	156810	171188	32%	86576	61244	1
19.09-2017 11:00	1305804400	232621	183500	15%	\$20079	172424	50%	88777	61767	
19.09.2017 12:00	1505808000	138569	181663	16%	123011	173163	29%	91080	61555	
19.09.201713:00	1505811600	257122	182977	16%	124475	170644	27%	.91441	61662	
19.09.2017.14:00	1505815200	255135	181081	17%	122487	170854	28%	91918	61139	
19.09.2017 15:00	1505818800	154502	184338	46%	120164	172215	30%	99975	60720	
19.09.2017.16.00	1505822400	133061	288944	54%	120707	168027	28%	99871	60720	
19.09.2017 17:00	1505816000	137144	275753	50%	118718	166457	29%	81882	59359	
19.09.2017 18:00	1505819600	134736	272613	51%	117985	163526	28%	87521	56535	
19.09.2017.19:00	1505833200	136201	140787	43%	103015	162060	36%	86768	39575	
19.09.2017.20:00	1505836800	135573	155657	42%	97562	161118	40%	87511	50251	
19.09.2017 21:00	1505840400	134945	152097	42%	96001	158396	39%	\$7207	49625	
19.09.2017 22:00	1505844000	137144	125188	39%	95562	151277	57%	86693	49623	
19.09.2017 23:00	1505847600	136097	116499	57%	#3802	147613	36%	85950	43995	
7-1-1-1-1-1	TOTAL IN KW/H	3932	5909		2548	3763		1977	1165	
- 1	Difference in XW/H	1977			1215			-813		
Total co	nsumbon OFF 24H					1 08 37				
Total c	onsumtion ON 24H					84 58				22%
Difference Kw/h t	otal 3 units in 24H					23 79				

Conclusion:

The *Smart Cooling*™ adiabatic pre-cooling system demonstrated a clear and measurable improvement in chiller efficiency during the testing period.

Across two comparable four-day cycles, the system reduced electrical consumption from **44,264 kWh OFF** to **34,955 kWh ON**, resulting in a total saving of **9,308 kWh** over the 4-day **ON** period.

Based on these results, the projected monthly savings amount to **69,195 kWh**, corresponding to **USD 7,611.45** at an electricity rate of **\$0.11/kWh**.

The reduction in energy use equates to a decrease of more than 13,000 pounds of CO₂ emissions per month.

Considering the achieved savings, the Return on Investment (ROI) for installing the *Smart Cooling* $^{\text{TM}}$ system at this site is estimated to be 12 months.

Smart Cooling[™] effectively lowered chiller energy consumption under similar temperature and humidity conditions, confirming its ability to enhance system efficiency and reduce operating costs.

Alexander Alzamora September 20, 2017